



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 8,100 BTU/hr
 SUCTION TEMP: 30° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .60A
 LED LIGHTS: 3.6A
 CONDENSATE PUMP: 1.0A
 TOTAL: 5.2A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 1 1/4HP COND. UNIT: 9.2A
 TOTAL: 16.4A
 MCA: 19.4A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

THIS EQUIPMENT IS INTENDED FOR THE STORAGE OF NON-POTENTIALLY-HAZARDOUS BOTTLED OR CANNED PRODUCTS ONLY



AUTHORIZATION (PRINT):		DATE:				SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 5-13-14		CHECKED BY:	
5-9-18	DRH	6FT HC BEVERAGE TALL							
8-28-17	DRH								
DATE	REV.	DWG.	INCH			DRAWING NUMBER			
REVISION	TOL:					P6661			